



HAS PROXIMITY READERS



P-500-HAS

P-300-HAS

P-640-HAS



HAS Proximity Readers



Frequency: 125 kHz

Read Ranges:

P-300-HAS: Up to 3.5 inches (89 mm)

P-500-HAS: Up to 4.25 inches (108 mm)

P-640-HAS: Up to 4.25 inches (108 mm)



ETL Listed — Independently Tested and Certified (Wiegand models)

Conform to UL Standard 294 and ULC 60839-11-1



Warranty

Lifetime Warranty



Wiegand, ABA Track II Magnetic Stripe or OSDP*

Output Interface



Contactless

Up to 4.25 in (108 mm)



Mullion Mount (P-300-HAS)

Metal Door, Window Frames & Flat Surfaces



U.S. Single-Gang Wall-Box Mount (P-500-HAS and P-640-HAS)

Metal or Plastic Box & Flat Surfaces

*OSDP readers are independent models and need to be appended with the suffix "-OSDP" when ordering (Example: P-300-HAS-OSDP).

HAS PROXIMITY READERS

The HAS Proximity Readers are specialty members of Farpointe Data's proximity family of readers. Based upon proven digital radio frequency identification (RFID) technology, they support certain Securakey™ proximity formats, certain HID® and AWID® 125-kHz proximity protocols, and certain native Pyramid proximity protocols. Allowing for both indoor and outdoor operation, the electronics are secured in tamper-resistant epoxy potting.

Specifications	P-300-HAS	P-500-HAS	P-640-HAS
Technology	Proximity		
Frequency	125 kHz		
Mounting	Mullions, including metal door and window frames, as well as flat surfaces	Metal or plastic US single-gang wall box, as well as flat surfaces	Metal or plastic US single-gang wall box, as well as flat surfaces
Dimensions	1.7" W × 3.2" H × 0.7" D (43 mm × 81 mm × 18 mm)	3" W × 4.6" H × 0.4" D (76 mm × 117 mm × 10 mm)	3" W × 4.6" H × 0.75" D (76 mm × 117 mm × 19 mm)
OEM Label Area Dimensions	0.9" W × 0.35" H (22.86 mm × 8.89 mm) with corner radius of 0.06" (1.5 mm)		
Weight	3 oz (85 g)	4 oz (113 g)	4 oz (113 g)
Certifications	FCC, ICC, CE, UL Standard 294, ULC 60839-11-1 ¹		
IP Code ²	IP67		
Voltage ³	+5 to 16 VDC		
Current Draw	0.07 to 0.110A		
Read Range ⁴	Up to 3.5 inches (88 mm)	Up to 4.25 inches (108 mm)	Up to 4.25 inches (108 mm)
Cabling ⁵	24 AWG minimum, multiconductor stranded with an overall foil shield		
Interface	Wiegand (26-bit and custom formats), ABA Track II magnetic stripe (clock and data) or OSDP ⁶		
Operating Temperature	-40° F to 149° F (-40° C to +65° C)		
Operating Humidity	0% to 90% relative humidity		
Color Options	Black snap-on cover included standard		
Audio Tone	Beeper included standard		
Indoor & Outdoor Installation	Electronics sealed in weather- and tamper-resistant epoxy potting		
Warranty	Limited lifetime warranty		
LED	Four-state standard (red, green, amber, and off)		
Keypad Output ⁷	N/A	N/A	Wiegand
Technologies Supported	Certain Securakey™ 125-kHz proximity formats + certain HID® 125-kHz Proximity protocols ⁸ + certain AWID® 125-kHz Proximity protocols ⁹ + native Pyramid 125-kHz proximity protocols ¹⁰		

NOTES:

- Carrying the ETL Label and tested by Intertek, conforms to UL Standard 294 and ULC Standard 60839-11-1. Only Wiegand models have been evaluated.
- Self evaluated.
- Linear power supplies are recommended for best operation.
- Using PSC-1 Standard Light Proximity Card with 12 VDC at the reader.
- For example, Belden 9535 or similar, supporting the five conductors comprising the physical layer of the Wiegand interface (power, ground, data 0, data 1, and/or beeper and LED). Alternatively, Belden 9539 or similar, for all reader functions. Shielded, twisted pair (Belden 8723 or similar) for OSDP. Contact your access control system manufacturer for their specific requirements.
- OSDP readers are independent models and need to be appended with the suffix "-OSDP" when ordering (Example: P-300-HAS-OSDP).
- Available only on P-640-HAS model; 8-Bit Burst Wiegand standard. For 4-Bit Burst and other options, please contact Farpointe Data, Inc. Features may vary based on model.
- Examples may include, and may not be limited to, ProxCard II®, ISOProx® II, and ProxKey® II.
- Examples may include, and may not be limited to, CS Prox Card, GR (ISO) Graphics Quality Prox Card, and KT Key Tag.
- Examples may include, and may not be limited to, PSC-1, PSI-4, PSM-2, PSK-3, and PDT-1.



Specific features may vary by model.

Farpointe Data reserves the right to change specifications without notice.

© 2019-2021 Farpointe Data, Inc. All rights reserved. Farpointe Data®, Pyramid Series Proximity®, Delta®, Ranger®, and CONEKT® are the registered U.S. trademarks of Farpointe Data, Inc. Securakey is a trademark of Secura Key, a Division of Soundcraft, Inc. HID, the HID logo, ProxCard II, ISOProx, and ProxKey are registered trademarks of HID Global Corporation, an ASSA ABLOY company. All other trademarks are the property of their respective owners.

Farpointe Data, Inc.
2195 Zanker Road
San Jose, CA 95131 USA
Office: +1-408-731-8700
Fax: +1-408-731-8705
support@farpointedata.com



Apr-26-2021

www.farpointedata.com

P/N: 01148-002 · Rev. 2