



CSR-35 CONEKT™ MOBILE-READY CONTACTLESS SMARTCARD READER



Mounts to mullion

Mounts to single-gang wall switch box

Conekt Mobile Smartphone Access Control Solution



Frequency: 13.56 MHz and 2.4 GHz

Read Range:

Physical Credentials: Up to 1.5 inches (38 mm)

Mobile Credentials:

CSR-35P: Upon presentation up to 1.5 inches (38 mm)

CSR-35L: Up to 15 feet (4.6 m)



Bluetooth Low Energy

Supports Conekt Smartphone Mobile Access Credentials



Optimized for MIFARE® DESFire® EV1 & EV2

Integrated High-Security Contactless Smartcard Support



MAXSecure™

Unique Security Feature



ValidID™

Fraudulent Data Detection Solution



Warranty

Farpointe Lifetime Warranty



Wiegand or OSDP

Output Interface



Single Reader for Mullion or Wall-Switch Mount

Metal Door, Window Frames & Flat Surfaces

CSR-35 CONEKT™ MOBILE-READY CONTACTLESS SMARTCARD READER

Conekt comprises Farpointe Data’s contactless smartcard reader solution with mobile access support. Based upon the proven LEGIC® contactless digital radio frequency identification (RFID) platform, Conekt readers interface with a wide range of electronic access control systems by complying with either the legacy Wiegand or bi-directional Open Supervised Device Protocol (OSDP). They offer value-add features such as MAXSecure™ and ValidID™, and support both sector and card serial number (CSN) reads. In addition to traditional contactless smartcard access credentials, such as clamshell cards and key tags, the platform also offers the option of mobile access credentials loaded on Bluetooth Low Energy (BLE)-enabled smartphones. This allows the smartphone to function as a contactless electronic access control credential. Conekt access credentials, both traditional and mobile, can be ordered programmed to various formats in exact number sequence required.

Specifications	CSR-35 Conekt Mobile-Ready Contactless Smartcard Reader
Models	CSR-35P Presentation Mobile-Ready Contactless Smartcard Reader CSR-35L Long-Range Mobile-Ready Contactless Smartcard Reader
Technology ¹	Contactless smartcard and Bluetooth Low Energy (BLE)
Frequency	13.56 MHz (contactless smartcard) and 2.4 GHz (BLE)
Mounting	A single reader for metal door and window frames, single-gang wall boxes, and flat surfaces
Dimensions	Mullion: 1.7" W x 4.7" H x 1.2" D (43 mm x 119 mm x 30 mm) Switch Plate: 3" W x 5.1" H x 1.2" D (76 mm x 130 mm x 30 mm)
OEM Label Area	Backlit; Dimensions 0.9" W x 0.35" H (22.86 mm x 8.89 mm) with corner radius of 0.06" (1.5 mm)
Certifications	FCC, ICC, CE
IP Code ²	IP67
Voltage ³	+8 – 14 VDC
Current Draw	40 mA typical @ 12 VDC, 195 mA peak
Read Range ⁴	Physical Credentials: up to 1.5 inches (38 mm) Mobile Credentials: CSR-35P: Upon presentation up to 1.5 inches (38 mm) CSR-35L: Up to 15 feet (4.6 m)
Cabling ⁵	24 AWG minimum, multiconductor stranded with an overall foil shield
Interface	Wiegand (26-bit and custom formats), ABA Track II magnetic stripe (clock and data) or OSDP
Operating Temperature	-40° F to 149° F (-40° C to +65° C)
Audio Tone	Beeper included standard
Indoor & Outdoor Installation	Electronics sealed in weather- and tamper-resistant epoxy potting
Warranty	Limited lifetime warranty
LED	Five-state standard (blue, red, green, amber, and off)
Technologies Supported	Interoperable with CSN ⁶ (may include ISO 14443 compliant credentials and MIFARE® Classic 1k & 4k, MIFARE® DESFire® EV1 & EV2, MIFARE UltraLight® and MIFARE Plus®), and Sector (may include Delta Card Sector ⁷ , such as MIFARE® Classic 1k & 4k, MIFARE® DESFire® EV1 & EV2, as well as FIPS201 [PIV Type A], TWIC, and CAC credentials), as well as Conekt Mobile Access Credentials.

NOTES:

- 1 Optimized for use with devices supporting BLE version 4.2.
- 2 Self evaluated.
- 3 Linear power supplies are recommended for best operation.
- 4 Using DC1-1 Delta Clamshell Contactless Smartcard with 12 VDC at the reader. Other credentials may be less. Read ranges are further subject to the type of smartphone used, the manner in which it is used, as well as the installation and its environment.
- 5 For example, Belden 9535 or similar, supporting the five conductors comprising the physical layer of the Wiegand interface (power, ground, data 0, data 1, and/or beeper and LED). Alternatively, Belden 9539 or similar, for all reader functions. Contact your access control system manufacturer for their specific requirements.
- 6 CSN = Card Serial Number.
- 7 Examples include, but are not limited to, DC1-1, DM1-3, and DK1-3.

Patent Pending

Farpointe Data reserves the right to change specifications without notice.

© 2018-2019 Farpointe Data, Inc. All rights reserved. Farpointe Data®, Pyramid Series Proximity®, Delta®, and Ranger® are the registered U.S. trademarks of Farpointe Data, Inc. Conekt is a trademark of Farpointe Data, Inc. LEGIC is a registered trademark of LEGIC Identsystems Ltd. MIFARE®, MIFARE DESFire®, MIFARE UltraLight®, and MIFARE Plus® are registered trademarks of NXP B.V. All other trademarks are the property of their respective owners.

Farpointe Data, Inc.
2195 Zanker Road
San Jose, CA 95131 USA
Office: +1-408-731-8700
Fax: +1-408-731-8705
support@farpointedata.com

