



# GUARDIAN CONTACTLESS SMARTCARD READERS



D-405

D-410

D-403



## Guardian Vandal Resistant



**Frequency:** 13.56 MHz

**Read Ranges:**

D-403: Up to 1.5 inches (38 mm)

D-405: Up to 3 inches (76 mm)

D-410: Up to 3 inches (76 mm)



**MIFARE<sup>®</sup> DESFire<sup>®</sup> EV1 Support**  
High-Security Encryption Technology



**MAXSecure<sup>™</sup>**  
Unique Security Feature



**ValidID<sup>™</sup>**  
Fraudulent Data Detection Solution



**Warranty**  
Lifetime Warranty



**Wiegand**  
Output Interface



**Mullion Mount (D-403)**  
Metal Door, Window Frames & Flat Surfaces



**U.S. Single-Gang (D-405) & Double-Gang (D-410) Wall-Box Mount**  
Metal or Plastic Box & Flat Surfaces



**Vandal Resistant**  
Impact Resistant

# GUARDIAN CONTACTLESS SMARTCARD READERS

Guardian vandal-resistant readers are manufactured from thick polycarbonate material, feature epoxy potted electronics, and ship standard with tamperproof screws. Guardian readers are ideal for installations where more durability is required than the standard contactless smartcard reader. Such installations include schools, inner-city environments, correctional facilities, or sites where heavy machinery is operated.

Specifications	D-403	D-405	D-410
Technology	Contactless smartcard		
Frequency	13.56 MHz		
Mounting <sup>1</sup>	Mullions, including metal door and window frames, as well as flat surfaces	Metal or plastic US single-gang wall box, as well as flat surfaces	Metal or plastic US double-gang wall box, as well as flat surfaces
Dimensions	2" W x 5.25" H x 1" D (51 mm x 133 mm x 25 mm)	3" W x 4.5" H x 1" D (76 mm x 114 mm x 25 mm)	5" H x 5" W x 1" D (127 mm x 127 mm x 25 mm)
OEM Label Area Dimensions	0.9" W x 0.35" H (22.86 mm x 8.89 mm) with corner radius of 0.63" (16 mm)		
Weight	6 oz (170 g)	8 oz (227 g)	13 oz (369 g)
Certifications	FCC, ICC, CE		
IP Code <sup>2</sup>	IP67		
Voltage <sup>3</sup>	+5 – 14 VDC		
Current Draw	135 mA typical @ 12 VDC		
Read Range <sup>4</sup>	Up to 1.5 inches (38 mm)	Up to 3 inches (76 mm)	Up to 3 inches (76 mm)
Cabling <sup>5</sup>	24 AWG minimum, multiconductor stranded with an overall foil shield		
Interface	Wiegand, ABA Track II		
Operating Temperature	-40° F to 149° F (-40° C to +65° C)		
Color Options	Black		
Audio Tone	Beeper included standard		
Indoor & Outdoor Installation	Electronics sealed in weather- and tamper-resistant epoxy potting		
Warranty	Limited lifetime warranty		
LED	Four-state standard (red, green, amber, and off)		
Technologies Supported <sup>6</sup>	<p>CSN<sup>7</sup>: Supports CSN-only reading of certain credentials making use of ISO 14443 and ISO 15693 compliant protocols.</p> <p>Sector: Supports CSN + Sector (may include Delta Card Sector<sup>8</sup>, as well as FIPS201 [PIV Type A &amp; B], TWIC, and CAC credentials) reading of certain credentials making use of ISO 14443 and ISO 15693 compliant protocols.</p>		

**NOTES:**

- 1 Spacer included standard for installations on metal. Depending on environment, additional spacing may be required.
- 2 Self evaluated.
- 3 Linear power supplies are recommended for best operation.
- 4 Using DC1-1 Delta Clamshell Contactless Smartcard with 12 VDC at the reader. Other credentials may be less.
- 5 For example, Belden 9535 or similar.
- 6 Technologies supported may include MIFARE® Classic, MIFARE® DESFire® EV1, MIFARE UltraLight® and MIFARE® Plus, as well as other credential types.
- 7 CSN = Card Serial Number.
- 8 Examples include, but are not limited to, DC1-1, DM1-3, and DK1-3.

Farpointe Data reserves the right to change specifications without notice.

© 2017 Farpointe Data, Inc. All rights reserved. Farpointe Data®, Pyramid Series Proximity®, Delta®, and Ranger® are the registered U.S. trademarks of Farpointe Data, Inc. MIFARE, MIFARE DESFire, MIFARE UltraLight, and MIFARE Plus are registered trademarks of NXP B.V. All other trademarks are the property of their respective owners.

**Farpointe Data, Inc.**  
 1376 Borregas Avenue  
 Sunnyvale, CA 94089-1004 USA  
 Office: +1-408-731-8700  
 Fax: +1-408-731-8705  
 support@farpointedata.com

