



DC1-1 CLAMSHELL SMARTCARD



Delta[®] Contactless Smartcard



Frequency: 13.56 MHz
Read Range: Up to 3 inches (76 mm)



MAXSecure™
Unique Security Feature



ValidID™
Fraudulent Data Detection Solution



Warranty
Lifetime Warranty



Wiegand
Output Interface



Slot-Punch
Standard Vertical Slot



Contactless
Up to 3 in (76 mm)

DC1-1 CLAMSHELL SMARTCARD

Delta comprises Farpointe Data's 13.56 MHz line of contactless smartcard readers, cards, and tags. Based upon proven MIFARE® contactless digital radio frequency identification (RFID) technology, Delta readers interface with a wide range of electronic access control systems by complying with the Wiegand communication protocol. They offer value-add features such as MAXSecure™ and ValidID™. Additionally, Delta cards and tags are passive devices, eliminate maintenance by requiring no battery, and can be ordered programmed to various formats and encryption keys.

Specifications	DC1-1
Technology	Smartcard
Frequency	Excitation (13.56 MHz)
Operation	Passive (no battery)
Type	Clamshell card
Formats	Wiegand (26-bit and custom formats) and ABA Track II magnetic stripe (clock and data)
Material	ABS
Color	Off-white
Slot Punch	Standard, vertical slot
Marking ¹	Date code and ID
Imaging ²	Use a glossy adhesive overlay for color dye sublimation printing or print directly on card
Read Range ³	Up to 3 inches (76 mm)
Outputs ⁴	CSN and Sector
Options ⁵	Custom printing of company logos, URL, telephone number, and more
Warranty	Limited lifetime warranty
OEM Label Area Dimensions	0.11" W × 0.25" H (2.8 mm × 6.3 mm) with corner radius of 0.63" (16 mm)
Dimensions	2.2" W × 3.4" H × .06" D (56 mm × 86 mm × 1.5 mm)
Weight	0.3 oz (9 g)
Operating Temperature	-35° F to 122° F (-37° C to +50° C)
Humidity	0-95% non-condensing
Memory	1K memory standard ⁶
ISO Standards	Technology: ISO 14443
Technologies Supported	MIFARE® Classic

NOTES:

- 1 Matching internal and external sequential coding standard. Custom printing available.
- 2 Please verify that the printer (or overlay) supports credential type/thickness.
- 3 Tested with 12 VDC @ Delta5 reader. Reference Card Read Range Document for additional read range information.
- 4 CSN = Card Serial Number. Sector = access control data, such as format, facility code, and ID.
- 5 Contact Farpointe to learn how you can customize your cards and tags.
- 6 Other memory sizes available.

Farpointe Data reserves the right to change specifications without notice.

© 2012-2018 Farpointe Data, Inc. All rights reserved. Farpointe Data®, Pyramid Series Proximity®, Delta®, and Ranger® are the registered U.S. trademarks of Farpointe Data, Inc. MIFARE is a registered trademark of NXP B.V. All other trademarks are the property of their respective owners.

Farpointe Data, Inc.
 1376 Borregas Avenue
 Sunnyvale, CA 94089-1004 USA
 Office: +1-408-731-8700
 Fax: +1-408-731-8705
 support@farpointedata.com

