



DE2

MIFARE[®] DESFire[®] EV2 SMARTCARD



Delta[®] Contactless Smartcard



Frequency: 13.56 MHz
Read Range: Up to 2.5 inches (64 mm)



MIFARE[®] DESFire[®] EV2 Support
High-Security Encryption Technology



MAXSecure[™]
Unique Security Feature



ValidID[™]
Fraudulent Data Detection Solution



Warranty
One-Year Warranty



Wiegand
Output Interface



Slot-Punch
Vertical & Horizontal Indicators



Contactless
Up to 2.5 in (64 mm)

DE2 MIFARE® DESFire® EV2 SMARTCARD

Delta comprises Farpointe Data's 13.56 MHz line of contactless smartcard readers, cards, and tags. Based upon proven MIFARE® contactless digital radio frequency identification (RFID) technology, Delta readers interface with a wide range of electronic access control systems by complying with the Wiegand communication protocol. They offer value-add features such as MAXSecure™ and ValidID™, and now optional MIFARE® DESFire® EV2 application support. Additionally, Delta cards and tags are passive devices, eliminate maintenance by requiring no battery, and can be ordered programmed to various formats and encryption keys.

Specifications	DE2
Technology	Smartcard
Frequency	Excitation (13.56 MHz)
Operation	Passive (no battery)
Type	Dye sublimation
Formats	Wiegand (26-bit and custom formats) and ABA Track II magnetic stripe (clock and data)
Material	Composite PET plastic
Color	Glossy white
Slot Punch	Vertical and horizontal indicators
Marking ¹	Date code and ID
Imaging ²	Supports dye sublimation imaging
Read Range ³	Up to 2.5 inches (64 mm)
Outputs ⁴	Multi-Application
Options ⁵	Custom printing of company logos, URL, telephone number, and more
Warranty	12 months
OEM Label Area Dimensions	N/A
Dimensions	2.1" W × 3.4" H × 0.031" D (53 mm × 86 mm × 0.79 mm)
Weight	0.23 oz (6.4 g)
Operating Temperature	-31° F to 158° F (-35° C to +70° C)
Humidity	0-95% non-condensing
Memory	2-Kbyte EEPROM with fast programming
ISO Standards	Technology: ISO 14443 Size: ISO 7810

NOTES:

- 1 Matching internal and external sequential coding standard. Custom printing available.
- 2 Please verify that the printer (or overlay) supports credential type/thickness.
- 3 Tested with 12 VDC @ Delta5 reader. Reference Card Read Range Document for additional read range information.
- 4 Typical directory structure of up to 28 applications, with up to 32 files per application.
- 5 Contact Farpointe to learn how you can customize your cards and tags.

Farpointe Data reserves the right to change specifications without notice.

© 2018-2019 Farpointe Data, Inc. All rights reserved. Farpointe Data®, Pyramid Series Proximity®, Delta®, and Ranger® are the registered U.S. trademarks of Farpointe Data, Inc. Conekt is a trademark of Farpointe Data, Inc. MIFARE and MIFARE DESFire are registered trademarks of NXP B.V. All other trademarks are the property of their respective owners.

Farpointe Data, Inc.
 2195 Zanker Road
 San Jose, CA 95131 USA
 Office: +1-408-731-8700
 Fax: +1-408-731-8705
 support@farpointedata.com

