




# DM1-3 IMAGEABLE SMARTCARD



## Delta<sup>®</sup> Contactless Smartcard

 **Frequency:** 13.56 MHz  
**Read Range:** Up to 2.75 inches (70 mm)



**MIFARE<sup>®</sup> DESFire<sup>®</sup> EV1 Support**  
High-Security Encryption Technology



**MAXSecure<sup>™</sup>**  
Unique Security Feature



**ValidID<sup>™</sup>**  
Fraudulent Data Detection Solution



**Warranty**  
One-Year Warranty



**Wiegand**  
Output Interface



**Slot-Punch**  
Vertical & Horizontal Indicators



**Contactless**  
Up to 2.75 in (70 mm)

## DM1-3 IMAGEABLE SMARTCARD

Delta comprises Farpointe Data's 13.56 MHz line of contactless smartcard readers, cards, and tags. Based upon proven MIFARE® contactless digital radio frequency identification (RFID) technology, Delta readers interface with a wide range of electronic access control systems by complying with the Wiegand communication protocol. They offer value-add features such as MAXSecure™ and ValidID™, and now optional MIFARE® DESFire® EV1 application support. Additionally, Delta cards and tags are passive devices, eliminate maintenance by requiring no battery, and can be ordered programmed to various formats and encryption keys.

Specifications	DM1-3
Technology	Smartcard
Frequency	Excitation (13.56 MHz)
Operation	Passive (no battery)
Type	Dye sublimation
Formats	Wiegand (26-bit and custom formats) and ABA Track II magnetic stripe (clock and data)
Material	PVC
Color	Glossy white
Slot Punch	Vertical and horizontal indicators
Marking <sup>1</sup>	Date code and ID
Imaging <sup>2</sup>	Supports dye sublimation imaging
Read Range <sup>3</sup>	Up to 2.75 inches (70 mm)
Outputs <sup>4</sup>	CSN, Sector and Application
Options <sup>5</sup>	Custom printing of company logos, URL, telephone number, and more
Warranty	12 months
OEM Label Area Dimensions	N/A
Dimensions	2.1" W × 3.4" H × 0.031" D (53 mm × 86 mm × 0.79 mm)
Weight	0.19 oz (5.4 g)
Operating Temperature	-35° F to 122° F (-37° C to +50° C)
Humidity	0-95% non-condensing
Memory	1K memory standard <sup>6</sup>
ISO Standards	Technology: ISO 14443 Size: ISO 7810

### NOTES:

- 1 Matching internal and external sequential coding standard. Custom printing available.
- 2 Please verify that the printer (or overlay) supports credential type/thickness.
- 3 Tested with 12 VDC @ Delta5 reader. Reference Card Read Range Document for additional read range information.
- 4 CSN = Card Serial Number. Sector = access control data, such as format, facility code, and ID.  
Application = Typical directory structure of up to 28 applications, with up to 32 files per application.
- 5 Contact Farpointe to learn how you can customize your cards and tags.
- 6 Other memory sizes available.

Farpointe Data reserves the right to change specifications without notice.

© 2012-2016 Farpointe Data, Inc. All rights reserved. Farpointe Data®, Pyramid Series Proximity®, Delta®, and Ranger® are the registered U.S. trademarks of Farpointe Data, Inc. MIFARE is a registered trademark of NXP B.V. All other trademarks are the property of their respective owners.

**Farpointe Data, Inc.**  
 1376 Borregas Avenue  
 Sunnyvale, CA 94089-1004 USA  
 Office: +1-408-731-8700  
 Fax: +1-408-731-8705  
 support@farpointedata.com

