




DELTA5.3 CONTACTLESS SMARTCARD READER



Delta® Contactless Smartcard

 **Frequency:** 13.56 MHz
Read Range: Up to 1.5 inches (38 mm)



MIFARE® DESFire® EV1 Support
High-Security Encryption Technology



MAXSecure™
Unique Security Feature



ValidID™
Fraudulent Data Detection Solution



Warranty
Lifetime Warranty



Wiegand
Output Interface



European/Asian Wall-Box Mount
Box & Flat Surfaces

DELTA5.3 CONTACTLESS SMARTCARD READER

Delta comprises Farpointe Data's 13.56 MHz line of contactless smartcard readers, cards, and tags. Based upon proven MIFARE® contactless digital radio frequency identification (RFID) technology, Delta readers interface with a wide range of electronic access control systems by complying with the Wiegand communication protocol. They offer value-add features such as MAXSecure™ and ValidID™, and support sector and card serial number (CSN) reads. Additionally, Delta cards and tags are passive devices, eliminate maintenance by requiring no battery, and can be ordered programmed to various formats and encryption keys.

Specifications	Delta5.3
Technology	Contactless smartcard
Frequency	13.56 MHz
Mounting ¹	European or Asian single-gang wall box, as well as flat surfaces
Dimensions	3.25" W × 3.25" H × 0.8" D (83 mm × 83 mm × 20 mm)
OEM Label Area Dimensions	0.9" W × 0.35" H (22.86 mm × 8.89 mm) with corner radius of 0.63" (16 mm)
Weight	4 oz (113 g)
Certifications	FCC, ICC, CE
IP Code ²	IP67
Voltage ³	+5 – 14 VDC
Current Draw	135 mA typical @ 12 VDC
Read Range ⁴	Up to 1.5 inches (38 mm)
Cabling ⁵	24 AWG minimum, multiconductor stranded with an overall foil shield
Interface	Wiegand ABA Track II
Operating Temperature	-40° F to 149° F (-40° C to +65° C)
Color Options	A black snap-on cover included standard
Audio Tone	Beeper included standard
Indoor & Outdoor Installation	Electronics sealed in weather- and tamper-resistant epoxy potting
Warranty	Limited lifetime warranty
LED	Four-state standard (red, green, amber, and off)
Technologies Supported ⁶	Delta5.3-CSN ⁷ : Supports CSN-only reading of certain credentials making use of ISO 14443 and ISO 15693 compliant protocols. Delta5.3-Sector: Supports CSN + Sector (may include Delta Card Sector ⁸ , as well as FIPS201 [PIV Type A & B], TWIC, and CAC credentials) reading of certain credentials making use of ISO 14443 and ISO 15693 compliant protocols.

NOTES:

- 1 Spacer included standard for installations on metal. Depending on environment, additional spacing may be required.
- 2 Self evaluated.
- 3 Linear power supplies are recommended for best operation.
- 4 Using DC1-1 Delta Clamshell Contactless Smartcard with 12 VDC at the reader. Other credentials may be less.
- 5 For example, Belden 9535 or similar.
- 6 Technologies supported may include MIFARE® Classic, MIFARE® DESFire® EV1, MIFARE UltraLight® and MIFARE® Plus, as well as other credential types.
- 7 CSN = Card Serial Number.
- 8 Examples include, but are not limited to, DC1-1, DM1-3, and DK1-3.

Farpointe Data reserves the right to change specifications without notice.

© 2012-2016 Farpointe Data, Inc. All rights reserved. Farpointe Data®, Pyramid Series Proximity®, Delta®, and Ranger® are the registered U.S. trademarks of Farpointe Data, Inc. MIFARE®, MIFARE DESFire®, MIFARE UltraLight®, and MIFARE Plus are registered trademarks of NXP B.V. All other trademarks are the property of their respective owners.

Farpointe Data, Inc.
 1376 Borregas Avenue
 Sunnyvale, CA 94089-1004 USA
 Office: +1-408-731-8700
 Fax: +1-408-731-8705
 support@farpointedata.com

