



P-620 DENALI MULLION-MOUNT READER & KEYPAD



Pyramid Series Proximity[®]



Frequency: 125 kHz
Read Range: Up to 5 inches (126 mm)



MAXSecure™
Unique Security Feature



fleaPower™
Energy-Conservation Technology



Pro-X™
Read-Range Boosting Technology



Warranty
Lifetime Warranty



Wiegand
Output Interface



Mullion Mount
Metal Door, Window Frames & Flat Surfaces

P-620 DENALI MULLION-MOUNT READER & KEYPAD

Pyramid Series Proximity® from Farpointe Data sets the electronic security benchmark for 125-kHz proximity readers, cards, and tags. Based upon proven contactless digital radio frequency identification (RFID) technology, Pyramid readers interface with a wide range of electronic access control systems by complying with the Wiegand communication protocol. They offer value-add features such as MAXSecure™ and fleaPower™, and can be ordered to support several proximity card and tag technologies. Additionally, Pyramid cards and tags are passive devices, eliminate maintenance by requiring no battery, and can be ordered to support several proximity reader technologies.

Specifications	P-620
Technology	Proximity
Frequency	125 kHz
Mounting	Mullions, including metal door and window frames, as well as flat surfaces
Dimensions	1.78" W × 6.1" H × 0.91" D (45 mm × 155 mm × 23 mm)
OEM Label Area Dimensions	0.9" W × 0.35" H (22.86 mm × 8.89 mm), with corner radius of 0.63" (16 mm)
Weight	4 oz (113 g)
Certifications ¹	FCC, ICC, CE, C-Tick
IP Code ²	IP67
Voltage ³	+5 – 16 VDC
Current Draw	70 mA typical, 110 mA peak @ 12 VDC
Read Range ⁴	Up to 5 inches (126 mm)
Cabling ⁵	24 AWG minimum, multiconductor stranded with an overall foil shield
Interface	Wiegand
Operating Temperature	–40° F to 149° F (–40° C to +65° C)
Color	Black snap-on cover included standard
Audio Tone	Beeper included standard
Indoor & Outdoor Installation	Electronics sealed in weather- and tamper-resistant epoxy potting
Warranty	Limited lifetime warranty
LED	Four-state standard (red, green, amber, and off)
Keypad Output ⁶	Wiegand
Technologies Supported	P-620: <i>Pyramid Series Proximity®</i> Cards and Tags ⁷ P-620-H: Pyramid + certain HID® 125-kHz Proximity protocols ⁸ P-620-A: Pyramid + certain AWID® 125-kHz Proximity protocols ⁹ P-620-H-A: Pyramid + certain HID® 125-kHz Proximity protocols + certain AWID® 125-kHz Proximity protocols

NOTES:

- 1 Certifications are pending.
- 2 Self evaluated.
- 3 Linear power supplies are recommended for best operation.
- 4 Using PSC-1 Standard Light Proximity Card with 12 VDC at the reader.
- 5 For example, Belden 9535 or similar, supporting the five conductors comprising the physical layer of the Wiegand interface (power, ground, data 0, data 1, and/or beeper and LED). Alternatively, Belden 9539 or similar, for all reader functions. Contact your access control system manufacturer for their specific requirements.
- 6 8-Bit Burst or 26-bit Wiegand standard, for 4-Bit Burst and other options, please contact Farpointe.
- 7 Examples may include, and may not be limited to, PSC-1, PSI-4, PSM-2, PSK-3, and PDT-1.
- 8 Examples may include, and may not be limited to, ProxCard II®, ISOProx® II, and ProxKey® II.
- 9 Examples may include, and may not be limited to, CS Prox Card, GR (ISO) Graphics Quality Prox Card, and KT Key Tag.

Farpointe Data reserves the right to change specifications without notice.

© 2016-2018 Farpointe Data, Inc. All rights reserved. Farpointe Data®, Pyramid Series Proximity®, Delta®, and Ranger® are the registered U.S. trademarks of Farpointe Data, Inc. AWID is a registered trademark of Applied Wireless Identifications Group. HID, the HID logo, ProxCard II, ISOProx, and ProxKey are registered trademarks of HID Global Corporation, an ASSA ABLOY company. All other trademarks are the property of their respective owners.

Farpointe Data, Inc.
 1376 Borregas Avenue
 Sunnyvale, CA 94089-1004 USA
 Office: +1-408-731-8700
 Fax: +1-408-731-8705
 support@farpointedata.com

