



P-710 ANDES PROXIMITY READER



Pyramid Series Proximity[®]



Frequency: 125 kHz
Read Range: Up to 15 inches (378 mm)



MAXSecure[™]
Unique Security Feature



fleaPower[™]
Energy-Conservation Technology



Pro-X[™]
Read-Range Boosting Technology



ETL Listed
Independently Tested and Certified to Conform to UL Standard 294



Warranty
Lifetime Warranty



Wiegand
Output Interface



U.S. Single-Gang Wall-Box Mount
Metal or Plastic Box & Non-Metallic Flat Surfaces

P-710 ANDES PROXIMITY READER

Pyramid Series Proximity® from Farpointe Data sets the electronic security benchmark for 125-kHz proximity readers, cards, and tags. Based upon proven contactless digital radio frequency identification (RFID) technology, Pyramid readers interface with a wide range of electronic access control systems by complying with the Wiegand communication protocol. They offer value-add features such as MAXSecure™ and fleaPower™, and can be ordered to support several proximity card and tag technologies. Additionally, Pyramid cards and tags are passive devices, eliminate maintenance by requiring no battery, and can be ordered to support several proximity reader technologies.

Specifications	P-710
Technology	Proximity
Frequency	125 kHz
Mounting	Metal or plastic US single-gang wall box, as well as non-metallic flat surfaces
Dimensions	6" W × 8.5" H × 1" D (216 mm × 152 mm × 25.4 mm)
OEM Label Area Dimensions	N/A
Weight	20 oz (567 g)
Certifications	FCC, ICC, UL Standard 294 ¹
IP Code ²	IP67
Voltage ³	+5 – 16 VDC
Current Draw	215 mA typical, 350 mA peak @ 12 VDC
Read Range ⁴	Up to 15 inches (378 mm)
Cabling ⁵	24 AWG minimum, multiconductor stranded with an overall foil shield
Interface	Wiegand ABA Track II
Operating Temperature	–40° F to 149° F (–40° C to +65° C)
Color Options	Black enclosure with a black label concealing mounting screws
Audio Tone	Beeper included standard
Indoor & Outdoor Installation	Electronics sealed in weather- and tamper-resistant epoxy potting
Warranty	Limited lifetime warranty
LED	Four-state standard (red, green, amber, and off)
Technologies Supported	P-710: Pyramid Series Proximity® Cards and Tags ⁶ P-710-H: Pyramid + certain HID® 125-kHz Proximity protocols ⁷ P-710-A: Pyramid + certain AWID® 125-kHz Proximity protocols ⁸ P-710-H-A: Pyramid + certain HID® 125-kHz Proximity protocols + certain AWID® 125-kHz Proximity protocols

NOTES:

- 1 Carrying the ETL Label and tested by Intertek, conforms to UL Standard 294.
- 2 Self evaluated.
- 3 Linear power supplies are recommended for best operation.
- 4 Using PSC-1 Standard Light Proximity Card with 12 VDC at the reader.
- 5 For example, Belden 9535 or similar.
- 6 Examples may include, and may not be limited to, PSC-1, PSI-4, PSM-2, PSK-3, and PDT-1.
- 7 Examples may include, and may not be limited to, ProxCard II®, ISOProx® II, and ProxKey® II.
- 8 Examples may include, and may not be limited to, CS Prox Card, GR (ISO) Graphics Quality Prox Card, and KT Key Tag.

Farpointe Data reserves the right to change specifications without notice.



© 2012-2016 Farpointe Data, Inc. All rights reserved. Farpointe Data®, Pyramid Series Proximity®, Delta®, and Ranger® are the registered U.S. trademarks of Farpointe Data, Inc. AWID is a registered trademark of Applied Wireless Identifications Group. HID, the HID logo, ProxCard II, ISOProx, and ProxKey are registered trademarks of HID Global Corporation, an ASSA ABLOY company. All other trademarks are the property of their respective owners.

www.farpointedata.com

Farpointe Data, Inc.
 1376 Borregas Avenue
 Sunnyvale, CA 94089-1004 USA
 Office: +1-408-731-8700
 Fax: +1-408-731-8705
 support@farpointedata.com