



REFERENCE DOCUMENT

125-kHz *PYRAMID SERIES* PROXIMITY[®]

READ RANGE DOCUMENT

All read ranges stated in the table below were tested with 12 VDC at the reader in a clean RF environment. Please note that read ranges stated are maximums [up to] and may be less than the range observed due to the unique characteristics of each individual installation. The read range is approximately equivalent for the various reader and card variants. For example, read range with the P-300 and PSC-1 will be very similar to that with the P-300-H and PSC-1-H.

Key: Inches (mm)

CREDENTIALS

	CREDENTIALS					
	PSC-1	PSK-3	PSI-4	PSM-2P PSM-2S	PDT-1	WRT-2+ ¹ WRT-4+
P-300	5 (126)	2.5 (63)	4 (101)	4 (101)	2.5 (63)	2.5 (63)
P-400	1 (25)	0.5 (13)	0.5 (13)	0.5 (13)	0.5 (13)	0.5 (13)
P-403	5 (126)	2.5 (63)	4 (101)	4 (101)	2.5 (63)	2.5 (63)
P-405	5 (126)	2.5 (63)	4 (101)	4 (101)	2.5 (63)	2.5 (63)
P-410	8 (202)	3.5 (88)	7 (176)	7 (176)	3.5 (88)	3.5 (88)
P-453	1 (25)	0.5 (13)	0.5 (13)	0.5 (13)	0.5 (13)	0.5 (13)
P-455	1 (25)	0.5 (13)	0.5 (13)	0.5 (13)	0.5 (13)	0.5 (13)
P-500	8 (202)	3.5 (88)	7 (176)	7 (176)	3.5 (88)	3.5 (88)
P-530	5 (126)	2.5 (63)	4 (101)	4 (101)	2.5 (63)	2.5 (63)
P-620	5 (126)	2.5 (63)	4 (101)	4 (101)	2.5 (63)	2.5 (63)
P-640	7 (176)	3 (76)	6 (151)	6 (151)	3 (76)	3 (76)
P-710	15 (378)	7 (176)	11 (277)	11 (277)	7 (176)	7 (176)
P-900	20 (504)	8 (202)	16 (403)	16 (403)	8 (202)	8 (202)

READERS

¹ Proximity insert only for both WRT-2+ and WRT-4+ transmitters

Farpointe Data reserves the right to change specifications without notice.

© 2012-2016 Farpointe Data, Inc. All rights reserved. Farpointe Data[®], Pyramid Series Proximity[®], Delta[®], and Ranger[®] are the registered U.S. trademarks of Farpointe Data, Inc. All other trademarks are the property of their respective owners.

Farpointe Data, Inc.
1376 Borregas Avenue
Sunnyvale, CA 94089-1004 USA
Office: +1-408-731-8700
Fax: +1-408-731-8705
support@farpointedata.com

