

THE READER

News for the Access Control Professional



AN INTRODUCTION TO WIEGAND



By Stephen "Shep" Sheppard
Key Accounts Sales Manager

Wiegand (pronounced wee-gand) is a standardized interface protocol commonly utilized to communicate data between a credential and a reader, as well as between a reader and a door controller, within the electronic access control (EAC) system environment.

[READ MORE](#)



Visit Farpointe
Data at ISC
East 2017

November 14 – 15
Javits Center, NY
Booth #848

[REGISTER FOR FREE](#)



Pictured: P-710 and P-900 Proximity Readers

Product Spotlight: Farpointe's High-Performance Proximity Readers

Have a site requiring the added convenience of longer read range?

- Senior care;
- Parking;
- Hospitals;
- Turnstiles;
- Airports.

With longer read ranges of up to 15 inches and 20 inches (378mm and 504mm) respectively, the high-performance P-710 and P-900 125-kHz proximity readers are backed by Farpointe's lifetime warranty and feature generous credential presentation targets.

For more details, download the following data sheets:

[P-710 DATA SHEET](#)

[P-900 DATA SHEET](#)



On Monday, September 3, 2018, Farpointe Data will be closed in celebration of the Labor Day holiday.



Farpointe Data
Readers • Credentials

© 2018 Farpointe Data, Inc. All rights reserved. Farpointe Data®, Pyramid Series Proximity®, Delta®, and Ranger® are the registered U.S. trademarks of Farpointe Data, Inc. All other trademarks are the property of their respective owners. Farpointe Data reserves the right to change specifications without notice.

Farpointe Data, Inc.
1376 Borregas Avenue
Sunnyvale, CA 94089-1004 USA
Office: +1-408-731-8700
Fax: +1-408-731-7805
support@farpointedata.com